

# 3M™ Dynatel™ 7500X and 7500XE Series Locator

## Technical Data Sheet



**7500X and 7500XE Locator**

### Description

3M™ Dynatel™ 7550X Series Locators  
3M™ Dynatel™ 7573X Series Locators

3M™ Dynatel™ 7550XE Series Locators  
3M™ Dynatel™ 7573XE Series Locators

The 3M Dynatel Pipe/Cable Locators 7500X and 7500XE Series are designed to equip a locate professional with the following technologies for underground locating and mapping:

- Receiver with Bluetooth® wireless technology
- Integrated USB port is compatible with USB Type-C® Connector
- Internal GPS that can be saved internally or directly to a memory stick that is compatible with USB Type-C® connector
- Write/read/locate 3M™ iD Markers
- Locate 3M™ Electronic Marker System (EMS)
- EMS Path Marking Antennas
- Multiple antennas for maximum locate capabilities
- Large LCD display with image driven graphical interface
- Integrated tone functions
- Sheath fault
- 12-Watt transmitter

Visit our website at [3m.co.uk/LocatingAndMarking](http://3m.co.uk/LocatingAndMarking) for product information.

### Agency Approvals and Self Certifications

For RoHS information, please visit [www.3M.com/ROHS](http://www.3M.com/ROHS)

Physical Specifications		
Receiver	Size (L x W x H) inch (cm)	Weight with batteries
Dynatel™ 7500X/7500XE Locators	30 x 6.5 x 10.5 (76.2 x 16.5 x 26.7)	6.4 lbs (2.9 kg)
Transmitter	Size (L x W x H) inch (cm)	Weight with batteries
Dynatel™ 7500/7500E Series	7.8 x 11.3 x 6.8 (19.7 x 28.6 x 17.2)	5.29 lbs (2.4 kg) (Alkaline) Rechargeable battery (2200RB) and Alkaline batteries: 9.2 lbs (4.2 kg)
Shipping Box	Size (L x W x H) inch (cm)	Weight with batteries
Dynatel™ 7550X/7550XE Series	33 x 17 x 12.5 (84 x 43 x 32)	28 lbs (12.7 kg)
Dynatel™ 7573X/7573XE Series	33 x 17 x 12.5 (84 x 43 x 32)	29 lbs (12.9 kg)

Environmental Specifications	
Operating Environment	Outdoor; Indoor for charging and configuring with a PC
Operating Temperature	-4° F to 122° F (-20° C to 50° C)
Storage Temperature	-4° F to 158° F (-20° C to 70° C)
Regulatory	3M™ Dynatel™ Locators 7550X/7573X Series (FCC Part 15) 3M™ Dynatel™ Locators 7550XE/7573XE Series (CE)
Environmental Standard	IP54
Maximum Altitude	6500 ft. (2000 m)

Receiver Electrical Specifications	
Power	3M™ Rechargeable Battery Pack (Alkaline 8xAA size battery pack for backup) <sup>1</sup>
Battery Life	8 hours typical <sup>2</sup>
Charging time	3 hours with 3A USB Type-C® Connector AC Adapter 15W <sup>3</sup>
Display	4.4" Diagonal LCD Display (Menu driven GUI)
Speaker	0.25W
Headphone Jack	Standard mini phone jack (used along with USB Type-C® adaptor)
Connectivity	Bluetooth® wireless technology - Dual-mode Bluetooth 5.0. Profiles support GAP, GATT, SPP. Bluetooth 5.0 wireless module at 2.4 GHz. USB port is compatible with USB Type-C® Connector.
GPS Mapping	GPS Interface (internal, 3 m) CEP50 (Autonomous Position Accuracy) External GPS Devices-Defer to Published Specifications of Device
Gain Control	Manual and Automatic
Cable/Pipe Depth Accuracy	±2% ± 3 inch (7.6 cm) for 0–60 inch (0 - 1.5 m) ±6% ± 3 inch (7.6 cm) for 60–120 inch (1.5–3.0 m) ±10% ± 3 inch (7.6 cm) for 120–180 inch (3.0 m–4.5 m)
Cable/Pipe Depth Range	0–360 inch (0–914 cm)
Marker Depth Accuracy	± 10% ± 2 inch (5 cm) up to specified depth of marker <sup>4</sup>
Locate Modes	Trace View, Directional Peak, Null (Provides 360° locate), Special Peak, Dual Peak
Notes:	
<sup>1</sup> It's recommended to use the rechargeable battery pack. However, a battery holder and adapter are provided for using 8-AA size Alkaline batteries for backup, which would have reduced battery life.	
<sup>2</sup> The battery life is specified for the 3M™ Rechargeable Battery Pack for the receiver at 73° F / 23° C, with 10% usage of the backlight and audio volume at medium level.	
<sup>3</sup> The unit will stop charging when unit temperature is 104° F (40° C) or higher and shuts off at 122° F (50° C)	
<sup>4</sup> Depth accuracy susceptible to high ambient noise conditions	

<b>Locate Frequencies</b>	
3M™ Transmitter* 7500 Series	577 Hz, 1 kHz, 8 kHz, 33 kHz, 82 kHz, 200 kHz
3M™ Transmitter* 7500E Series	577 Hz, 1 kHz, 8 kHz, 33 kHz, 82 kHz, 133 kHz
Passive	31.5 kHz (CATV) 15 – 30 kHz (LF)
Power	50 Hz, 5th and 9th harmonic of 50 Hz 60 Hz, 5th and 9th harmonic of 60 Hz (100 / 120 Hz) rectified power
Auxiliary	512 Hz 560 Hz 640 Hz
User Defined Frequencies	Four (50 Hz to 999 Hz)

\*Frequencies outputted by the 3M™ Transmitter Unit. Receiver only receives them.

<b>3M™ EMS Marker Frequencies</b>	
TEL: Telecommunications	101.4 kHz
PWR*: Power US	169.8 kHz
GAS: Gas	83.0 kHz
WTR: Water	145.7 kHz
WW: Wastewater/Sanitation	121.6 kHz
COM: CATV	77.0 kHz
GP: General Purpose/Reclaimed Water	66.35 kHz
CE PWR: European Power	134 kHz

\*Not available for XE-Models

<b>3M™ EMS Path Marking Tape &amp; Rope Frequencies</b>	
TEL: Telecommunications	48.8 kHz
PWR: Power US & European Power	34.9 kHz
GAS: Gas	53.9 kHz
WTR: Water	73.5 kHz
WW: Wastewater/Sanitation	41.4 kHz
RW: Reclaimed Water	44.9 kHz

<b>3M™ EMS (iD) Marker - Writing &amp; Reading Range</b>			
	<b>EMS Markers</b>		<b>EMS iD Marker</b>
<b>EMS (iD) Markers</b>	<b>Max Read Range:</b>	<b>Max Write Range:</b>	<b>Max Read Range:</b>
Near-Surface	3 ft (0.9 m)	6 inch (15 cm)	3 ft (0.9 m)
Ball Marker	6 ft (1.8 m)	12 inch (30 cm)	5 ft (1.5 m)
Mid-Range	7 ft. (2.1 m)	Not Applicable	Not Applicable
Full-Range	9 ft (2.8 m)	24 inch (60 cm)	8 ft (2.4 m)
<b>3M EMS Path Marking</b>	<b>Max Read Range:</b>		
7### Series Tape or Rope	4 ft (1.2 m)	Not Applicable	Not Applicable

Receiver Data Storage	
EMS-iD Read Records*	512
EMS-iD Program Records*	128
Locate Records*	512
Number of EMS-iD Templates:	80
<i>* no record limit with External flash drive. (only limited by flash drive size)</i>	

## Important Notice

---

**Technical Information:** The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

**Product Selection and Use:** Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product in accordance with all applicable instructions and with appropriate safety equipment, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

**Warranty, Limited Remedy, and Disclaimer:** Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement or repair of the 3M product or refund of the purchase price. Warranty claims must be made within one (1) year from the date of 3M's shipment.

**Limitation of Liability:** Except for the limited remedy stated above, and except to the extent prohibited by applicable law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

**Disclaimer:** 3M industrial and occupational products are intended, labelled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labelled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit [www.3M.com](http://www.3M.com).

---

## 3M Electrical Markets Division

3M Deutschland GmbH  
Carl-Schurz-Str.1  
41453 Neuss  
Germany

Reference: AABDD81827\_EN01  
Issue date: Jan 2022 – Supersedes New

© 3M 2022. 3M and Dynatel are trademarks of 3M. Used under license in Canada.  
The Bluetooth® word mark is a registered trademark owned by Bluetooth SIG, Inc.  
USB Type-C® is a registered trademark of USB Implementor Forum. All rights reserved.

